

ROBOSHOT S2000i - B

Specifications At-a-Glance

MODEL / Tonnage	Injection Size Range		Clamp Stroke		Max. Daylight		Min. Mold Thickness		Platen Size	
	oz	g	in	mm	in	mm	in	mm	in	mm
ROBOSHOT SiA 6	0.2	6.0	4.33	110	10.63	370	3.54	90	8.66 x 8.66	220 x 220
ROBOSHOT S2000i 17B	0.29 - 0.63	8.0 - 18.0	6.3	160	16.54	420	5.12	130	13.98 x 13.39	355 x 340
ROBOSHOT S2000i 33B	0.29 - 0.95	8.0 - 27.0	9.06	230	22.1	560	5.9	150	17.3 x 16.5	440 x 420
ROBOSHOT S2000i 55B	0.78 - 1.95	22.0 - 55.0	9.84	250	23.62	600	5.9	150	19.6 x 18.5	500 x 470
ROBOSHOT S2000i 110B	0.95 - 6.02	27.0 - 171.0	13.78	350	31.5	800	5.9	150	26.0 x 24.0	660 x 610
ROBOSHOT S2000i 165B - Micro	0.95 - 4.87	27.0 - 138.0	17.32	440	36.61	930	7.8	200	31.5 x 29.5	800 x 750
ROBOSHOT S2000i 165B	4.01 - 14.69	114.0 - 416.0	17.32	440	36.61	930	7.8	200	31.5 x 29.5	800 x 750
ROBOSHOT S2000i 275B	4.01 - 21.28	114.0 - 603.0	23.62	600	49.21	1250	11.8	300	40.6 x 37.8	1030 x 960
ROBOSHOT S2000i 330B	6.27 - 31.40	178.0 - 890.0	23.62	600	49.21	1250	11.8	300	44.5 x 40.6	1130 x 1030