



Safety Data Sheet

Issue Date: 01-Sep-2012

Revision Date: 23-Apr-2014

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Slide Quick Non-Chlorinated Mold Cleaner

Other means of identification

SDS # 40910H
Product Code 40910H
UN/ID No UN1950
Other Information Formula: 60114.

Recommended use of the chemical and restrictions on use

Recommended Use Aerosol spray lubricant.

Details of the supplier of the safety data sheet

Supplier Address

Slide Products Inc.
430 S. Wheeling Road
Wheeling, IL 60090

Emergency Telephone Number

Company Phone Number Phone: 1-847-541-7220
Fax: 1-847-541-7986
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Clear liquid in an aerosol

Physical State Aerosol

Classification

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Aerosols	Category 2

Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin

Signal Word

Danger

Hazard Statements

Causes skin irritation
May cause respiratory irritation. May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Flammable Aerosol

**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF ON SKIN: Wash with plenty of soap and water
 Take off contaminated clothing and wash it before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a poison center or doctor/physician if you feel unwell
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do not induce vomiting

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Very toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
N-Heptane	142-82-5	65-75
Propane	74-98-6	15-20
N-Butane	106-97-8	8-14

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash with soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If breathing is difficult, give oxygen. Call a physician if you feel unwell.
Ingestion	Do not induce vomiting. Drink plenty of water or milk immediately. Call a physician or poison control center immediately.

Most important symptoms and effects

Symptoms	Irritating to mouth, throat, and stomach if ingested. Overexposure by inhalation can cause headaches, nausea, dizziness, decreased blood pressure. May cause skin irritation and defatting of skin with repeated/prolonged contact. Exposed individuals may experience eye tearing, redness and discomfort.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO₂). Foam. Dry chemical. Water spray (fog).

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Aerosols may rupture violently at temperatures above 120 F. Aerosol flame projection test: >18" extension at 70 F. Pressurized container: May burst if heated. Vapors may form explosive mixture with air.

Hazardous Combustion Products Carbon oxides.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Use personal protective equipment as required.
-----------------------------	--

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Clean-Up	Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Wash thoroughly after handling. Use personal protection recommended in Section 8. Avoid breathing vapors or mists. Use only in well-ventilated areas. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Protect from direct sunlight. Do not store at temperatures above 120°F. Store away from sources of ignition. Store locked up.

Incompatible Materials

None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
N-Butane 106-97-8	TWA: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³

Appropriate engineering controls

Engineering Controls

Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Safety glasses.

Skin and Body Protection

Protective gloves are not required, but recommended.

Respiratory Protection

Ensure adequate ventilation, especially in confined areas.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Aerosol	Odor	Not determined
Appearance	Clear liquid in an aerosol	Odor Threshold	Not determined
Color	Not determined		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	71 °C / 159 °F	
Flash Point	Not available	
Evaporation Rate	Faster than ether	
Flammability (Solid, Gas)	Not determined	
Upper Flammability Limits	7.5%	
Lower Flammability Limit	1.2%	
Vapor Pressure	137 mm Hg	
Vapor Density	Heavier than air	
Specific Gravity	0.6288	(1=Water)
Water Solubility	None	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization	Hazardous polymerization does not occur.
---------------------------------	--

Conditions to Avoid

Do not puncture or incinerate cans. Avoid temperatures above 120°F.

Incompatible Materials

None known.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Avoid contact with eyes.
Skin Contact	May be harmful in contact with skin. Causes skin irritation.
Inhalation	Avoid breathing vapors or mists.
Ingestion	Do not taste or swallow.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
N-Heptane 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
N-Butane 106-97-8	-	-	= 658 mg/L (Rat) 4 h

Information on physical, chemical and toxicological effects

Symptoms	Please see section 4 of this SDS for symptoms.
-----------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity	This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.
STOT - single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
Aspiration hazard	May be fatal if swallowed and enters airways.

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
N-Heptane 142-82-5		375.0: 96 h Cichlid fish mg/L LC50		10: 24 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
N-Heptane 142-82-5	4.66
Propane 74-98-6	2.3
N-Butane 106-97-8	2.89

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
N-Heptane 142-82-5	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1950
 Proper Shipping Name Aerosols
 Hazard Class 2.1

IATA

UN/ID No UN1950
 Proper Shipping Name Aerosols, flammable
 Hazard Class 2.1

IMDG

UN/ID No UN1950
 Proper Shipping Name Aerosols
 Hazard Class 2.1
 Marine Pollutant This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

TSCA Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

SARA 313

Not determined

US State Regulations

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
N-Heptane 142-82-5	X	X	X
Propane 74-98-6	X	X	X
N-Butane 106-97-8	X	X	X

16. OTHER INFORMATION

NFPA**Health Hazards****Flammability****Instability****Special Hazards**

Not determined

Not determined

Not determined

Not determined

HMIS**Health Hazards****Flammability****Physical Hazards****Personal Protection**

1

4

0

B

Issue Date: 01-Sep-2012**Revision Date:** 23-Apr-2014**Revision Note:** New format**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet