

1. IDENTIFICATION

Product Identifier**Product Name** Slide Hi-Temp 1800 Mold Release**Other means of identification****SDS #** 44110**Product Code** 44110**UN/ID No** UN1950**Recommended use of the chemical and restrictions on use****Recommended Use** Mold Release.**Details of the supplier of the safety data sheet****Supplier Address**Slide Products Inc.
430 S. Wheeling Road
Wheeling, IL 60090**Emergency Telephone Number****Company Phone Number**

Phone: 1-847-541-7220

Fax: 1-847-541-7986

Emergency Telephone (24 hr)

INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Clear, oily, colorless liquid**Physical State** Aerosol**Odor** Slight ethereal**Classification**

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Flammable Aerosols	Category 2

Signal Word**Danger****Hazard Statements**

Harmful if inhaled

Causes serious eye irritation

Flammable Aerosol



Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Wash face, hands and any exposed skin thoroughly after handling
 Wear eye/face protection
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a poison center or doctor/physician
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a poison center or doctor/physician if you feel unwell

Precautionary Statements - Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Dimethyl ether	115-10-6	40-50
1,1 difluoroethane	75-37-6	40-50
Isopropanol	67-63-0	8-12
Butyl acetate	123-86-4	<2

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. Immediately call a poison center or doctor/physician.
Skin Contact	Wash with soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed. Call a poison center or doctor/physician if you feel unwell.
Ingestion	Do not induce vomiting. If conscious, give 1 glass of water or milk to dilute. Call a physician or poison control center immediately.

Most important symptoms and effects

Symptoms	Causes serious eye irritation. Exposed individuals may experience eye tearing, redness and discomfort. Concentrated spray may cause freezing of skin area. Skin contact can lead to drying, defatting, itching, stinging and irritation. Prolonged breathing of vapors may cause nausea, headache, weakness and/or dizziness. Irritating to mouth, throat, and stomach if ingested.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO₂). Foam. Dry chemical.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

This product is a flammable aerosol. Aerosols may rupture violently at temperatures above 120 F. Pressurized container: May burst if heated.

Hazardous Combustion Products Carbon oxides.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required.

Environmental Precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Wash thoroughly after handling. Use personal protection recommended in Section 8. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not drop.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Incompatible Materials Strong oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses.

Skin and Body Protection Wear suitable protective clothing.

Respiratory Protection Ensure adequate ventilation, especially in confined areas.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Aerosol	Odor	Slight ethereal
Appearance	Clear, oily, colorless liquid	Odor Threshold	Not determined
Color	Clear Colorless		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	< -45 °C / < -50 °F	
Boiling Point/Boiling Range	Not available	
Flash Point	Not available	
Evaporation Rate	Extremely rapid	
Flammability (Solid, Gas)	Flammable aerosol	
Upper Flammability Limits	25.0%	
Lower Flammability Limit	4.0%	
Vapor Pressure	Not available	
Vapor Density	Not available	
Specific Gravity	1.0	(1=Water)
Water Solubility	Partially soluble	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	
Bulk Density	8.37 lb/gal @ 60°F	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Do not puncture or incinerate cans. Avoid temperatures above 120 °F.

Incompatible Materials

Strong oxidizers.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes serious eye irritation.

Skin Contact Avoid contact with skin.

Inhalation Harmful if inhaled.

Ingestion Do not taste or swallow.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Dimethyl ether 115-10-6	-	-	= 308.5 mg/L (Rat) 4 h
Isopropanol 67-63-0	= 4396 mg/kg (Rat)	= 12800 mg/kg (Rat) = 12870 mg/kg (Rabbit)	= 72.6 mg/L (Rat) 4 h
Polyacrylic acid 9003-01-4	= 2500 mg/kg (Rat)	-	-
Butyl acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 391 ppm (Rat) 4 h

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Carcinogenicity**

Group 3 IARC components are "not classifiable as human carcinogens".

Chemical Name	ACGIH	IARC	NTP	OSHA
Isopropanol 67-63-0		Group 3		X

Legend**IARC (International Agency for Research on Cancer)**

Group 3 IARC components are "not classifiable as human carcinogens"

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION**Ecotoxicity**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Isopropanol 67-63-0	1000: 96 h <i>Desmodesmus subspicatus</i> mg/L EC50 1000: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	9640: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 11130: 96 h <i>Pimephales promelas</i> mg/L LC50 static 1400000: 96 h <i>Lepomis macrochirus</i> µg/L LC50		13299: 48 h <i>Daphnia magna</i> mg/L EC50
Polyacrylic acid 9003-01-4		580: 96 h <i>Lepomis macrochirus</i> mg/L LC50		168: 96 h water flea mg/L EC50
Butyl acetate 123-86-4	674.7: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	17 - 19: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 100: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 62: 96 h <i>Leuciscus idus</i> mg/L LC50 static	EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min EC50 = 959 mg/L 18 h EC50 = 98.9 mg/L 30 min	72.8: 24 h <i>Daphnia magna</i> mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Dimethyl ether 115-10-6	-0.18
Isopropanol 67-63-0	0.05
Butyl acetate 123-86-4	1.81

Other Adverse Effects

Not determined

Ozone

Contains no ozone depleting chemicals

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Isopropanol 67-63-0	Toxic Ignitable
Butyl acetate 123-86-4	Toxic

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1

IATA

UN/ID No	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.1

IMDG

UN/ID No	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1

15. REGULATORY INFORMATION**International Inventories**

TSCA All ingredients are listed or exempt from listing on Chemical Substance Inventory

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Isopropanol - 67-63-0	67-63-0	8-12	1.0

CWA (Clean Water Act)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl acetate 123-86-4 (<2)	5000 lb			X

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Dimethyl ether 115-10-6	X	X	X
1,1 difluoroethane 75-37-6	X	X	
Isopropanol 67-63-0	X	X	X
Butyl acetate 123-86-4	X	X	X

16. OTHER INFORMATION

NFPA**Health Hazards**

Not determined

Flammability

Not determined

Instability

Not determined

Special Hazards

Not determined

HMIS**Health Hazards**

1

Flammability

3

Physical Hazards

0

Personal Protection

B

Issue Date:

01-Sep-2012

Revision Date:

16-Jul-2014

Revision Note:

New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

