



# Safety Data Sheet

## Dynatex® 49433 Super Glue Gel

### Section 1. Identification

Product Identifier Dynatex® 49433 Super Glue Gel

Synonyms 49433CL12

Manufacturer Stock Numbers 49433CL12

Recommended use Refer to Technical Information

Uses advised against Refer to Technical Information

#### Manufacturer Contact

##### Address

Dynatex a division of Soudal Accumatic  
350 Ring Road  
Elizabethtown, KY, 42701  
USA

##### Phone

(270) 769-3385

##### Emergency Phone

(800) 424-9300

CHEMTREC

##### Fax

(270) 769-6418

### Section 2. Hazards Identification

#### Classification

EYE DAMAGE/IRRITATION - Category 2A  
FLAMMABLE LIQUIDS - Category 4  
SKIN CORROSION/IRRITATION - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3

#### Signal Word

Warning

#### Pictogram



Hazard Statements	Causes serious eye irritation Causes skin irritation Combustible liquid May cause respiratory irritation.
Precautionary Statements Response	Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If inhaled: Remove person to fresh air and keep comfortable for breathing. If on skin: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Read label before use. Take off contaminated clothing and wash it before reuse.
Prevention	Avoid breathing dust/fume/gas/mist/ vapors/spray. Keep away from heat. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Wear eye protection/face protection. Wear protective gloves. Wear protective gloves/eye protection/face protection
Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local, state and federal regulations.

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

Additional Information None known

### Section 3. Ingredients

CAS	Ingredient Name	Weight %
26915-72-0	Methoxy Polyethylene Glycol 1000 Methacrylate	0.1% - 1%
123-31-9	Hydroquinone	0.1% - Max
7085-85-0	Ethyl-2-Cyanoacrylate	50% - 100%

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-Aid Measures

**Eye Contact** Flush with warm water. If eyelids are bonded closed, release eyelashes with warm water by covering the eye with a wet pad. Do not force eye open. See

	supplemental section for emergency action.
Skin Contact	Soak in warm water. Do not pull skin apart. See supplemental section for emergency action.
Inhalation	Remove to fresh air. If symptoms persist, obtain appropriate medical attention.
Ingestion	Ingestion is unlikely. See supplemental section for emergency action.
First Aid Supplement	Cyanoacrylate adhesive is a very fast setting and strong adhesive. It bonds to human tissue and skin in seconds. Experience has shown that accidents due to Cyanoacrylates are best handled by passive, non-surgical first aid. Treatment of specific types of accidents are suggested as follows:
Skin Contact	Remove excess adhesive. Soak in warm, soapy water. The adhesive will come loose from the skin in several hours. Dried adhesive does not present a health hazard even when bonded to the skin. Avoid contact with clothes, fabrics, rags, or tissue. Contact with these materials may cause polymerization. The polymerization of large amounts of adhesive will generate heat causing smoke, skin burns, and strong, irritating vapors. Wear rubber or polyethylene gloves and an apron when handling large amounts of adhesive.
Skin Adhesion	First immerse the bonded surfaces in warm, soapy water. Peel off or roll the surfaces open with the end of a blunt edge, such as a spatula or a spoon handle, then remove adhesive with soap and water. Do not try to pull the surfaces apart with a direct opposing action.
Eyelid adhesion	In the event that eyelids are stuck together or bonded to the eyeball, wash thoroughly with warm water and apply a gauze patch. The eye will open without further action, typically in one to two days. There will be no residual damage. Do not try to pull the surfaces apart with a direct opposing action.
Adhesive in eye	Adhesive introduced into the eyes will attach itself to the eye protein and will disassociate from it over intermittent periods, usually several hours. This will cause periods of weeping until clearance is achieved. It is important to understand that disassociation will normally occur within a matter of hours, even with gross contamination.
Mouth	If lips are accidentally stuck together apply lots of warm water and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action. It is almost impossible to swallow cyanoacrylate. The adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in one to two days.
Burns	Cyanoacrylate gives off heat on solidification. In rare cases, large drops will increase in temperature enough to cause a burn. Burns should be treated normally after the lump of cyanoacrylate is released from the tissue as described above.
Surgery	It should never be necessary to use such drastic action to separate accidentally bonded skin.

## Section 5. Fire Fighting Measures

Suitable Extinguishing Media	Carbon Dioxide, Dry Chemical, Foam Use water fog to cool material in vicinity of fire.
Unsuitable Extinguishing Media	None known
Unusual Fire or Explosion Hazards	None known

## Section 6. Accidental Release Measures

**Steps to be taken in case of spill or release** Observe all personal protection equipment recommendations. Do not use cloths for clean up. Flood spilled material with water to polymerize. Cured material can be scrapped up and disposed of as nonhazardous waste. Make sure spill area is well ventilated.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable.

## Section 7. Handling and Storage

**Storage** Store away from heat and direct sunlight to maximize shelf life. Store inside in a dry location. Keep container tightly closed.

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapor or mist. Avoid contact with paper goods or fabric. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors.

## Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Methoxy Polyethylene Glycol 1000 Methacrylate	N/A	N/A	N/A
	Hydroquinone	2 mg/mm <sup>3</sup> A3	TWA 2 mg/mm <sup>3</sup>	N/A
	Ethyl-2-Cyanoacrylate	0.2 ppm	None	N/A

**Personal Protective Equipment** Goggles, Gloves

**Eye Protection** Safety goggles or glasses with side shields are recommended.

**Skin Protection** Polyethylene or non-reactive gloves. Do not use cotton, PVC or wool.

**Ventilation** Local exhaust ventilation is recommended to maintain vapor level below TLV.

**Respiratory Protection** Not applicable with good local exhaust. Use NIOSH approved respirator if there is a potential to exceed exposure limits.

## Section 9. Physical and Chemical Properties

Physical State	Liquid
Color	Colorless
Odor	Characteristic

Odor Threshold	Not determined
Solubility	Not miscible in water
Partition coefficient Water/n-octanol	Not determined
VOC%	< 20 g/L (estimated)
Viscosity	Not determined
Specific Gravity	1.05
Density lbs/Gal	8.762
Pounds per Cubic Foot	N/A
Flash Point	87C 189F
FP Method	N/A
Ph	Not determined
Melting Point	Undetermined
Boiling Point	>150C >302F
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not determined
Flammability	Not applicable
Decomposition Temperature	Not determined
Auto-ignition Temperature	Product is not self-igniting
Vapor Pressure	0.3 hPa @ 20C
Vapor Density	Not determined

Note The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

## Section 10. Stability and Reactivity

Chemical stability Stable under recommended storage conditions.  
Hazardous Polymerization Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.  
Materials to Avoid / Incompatibility Polymerized by contact with water, alcohols, amines, and alkalis.

## Section 11. Toxicological Information

Special Hazard Information No known applicable information.

on Components  
Component Toxicology Information No known applicable information.

## Section 12. Ecological Information

Fate and Effects in Waste Water Treatment Plants Complete information is not yet available.  
Environmental Effects Complete information is not yet available.  
Environmental Fate and Distribution Complete information is not yet available.

## Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

## Section 14. Transport Information

UN Number 1993  
UN Proper Shipping Name Combustible liquid, NOS (more the 450 liters)  
DOT Classification Unrestricted under 450 liters  
Packing Group N/A  
Air Shipment (IATA) Proper Shipping Name: Aviation regulation liquids, n.o.s. (Cyanoacrylate ester)  
Hazard Class or Division: 9  
Identification Number: UN3334  
Packing Group: None  
Exceptions: Unrestricted under 500 mL  
Ocean Shipment (IMDG) Proper Shipping Name: Unrestricted  
Hazard Class or Division: None  
Identification Number: None  
Packing Group: None  
Marine Pollutant: None

## Section 15. Regulatory Information

TSCA Status All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.  
SARA Title III Section 302 Extremely Hazardous Substances None

SARA Titre III Section 304 CERCLA Substances dangereuses	None
SARA Title III Section 312 Hazard Class	Acute: Yes Chronic: Yes Fire: Yes Pressure: No Reactive: Yes
SARA Title III Section 313 Toxic Chemicals	None present or none present in regulated quantities.
California Proposition 65	This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: Saccharin. Proper usage necessitates no Proposition 65 warning.
Massachusetts	No ingredient regulated by MA Right-to-Know Law present.
New Jersey	None known
Pennsylvania	None known

## Section 16. Other Information

Revision Date 12/21/2015

**Disclaimer** The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.