



SLIDE MOLD & METAL POLISH

Issue Date: 6-May-2015

Revision Date: 6-May-2015

Version 1

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

| | |
|-----------------|---------------------------|
| Chemical Name | Not applicable. |
| CAS No. | Mixture |
| Trade Name | Slide Mold & Metal Polish |
| Product Code(s) | 45202, 45210 |
| SDS # | 45202-45210 |

Relevant identified uses of the substance or mixture and uses advised against

| | |
|---------------------------|--|
| Identified Use(s) | Industrial Mold Cleaner and Polishing Compound |
| Uses Advised Against | None |
| Company Identification | Slide Products, Inc. 430 S. Weeling Rd. Wheeling, IL 60090 |
| Telephone | (847) 541-7220; 1-800-323-6433 (toll free) |
| E-Mail (competent person) | info@slideproducts.com |

Emergency telephone number

| | |
|---------------------|---|
| Emergency Phone No. | INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America) |
|---------------------|---|

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Skin Irrit. 2; STOT SE 3

Label elements

Hazard Symbol



WARNING

Signal Word(s)

Hazard Statement(s)

Causes skin irritation.
May cause drowsiness or dizziness.
May cause eye irritation.

Precautionary Statement(s)

Wear protective gloves/eye protection.
Avoid breathing vapors.
Wash hands and exposed skin after use.



SLIDE MOLD & METAL POLISH

Issue Date: 6-May-2015

Revision Date: 6-May-2015

Version 1

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Composition/information on ingredients | % wt. | CAS No. | Hazard classification |
|---|---------|------------|---|
| Naphtha, (petroleum), hydrotreated heavy | 10 - 20 | 64742-48-9 | Flam. Liq. 3; H226 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 2; H401 Aquatic Chronic 2; H411 |
| Solvent naphtha (petroleum), medium aliph. | 10 - 20 | 64742-88-7 | Flam. Liq. 3; H226 Skin Irrit. 2; H315 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Acute 2; H401 Aquatic Chronic 2; H411 |
| Amides, rape-oil, N-(hydroxyethyl), ethoxylated | 0.5 | 85536-23-8 | Skin Irrit. 2; H315 Eye Irrit. 2b; H320 Aquatic Acute 3; H402 Aquatic Chronic 3; H412 |
| Aluminum oxide | 30 | 1344-28-1 | Not classified as dangerous for supply/use. |
| Ammonium oleate | 10 - 15 | 544-60-5 | Not classified as dangerous for supply/use. |
| Iron oxide | 0.04 | 1309-37-1 | Not classified as dangerous for supply/use. |
| Water | 38 | 7732-18-5 | None |

Additional Information - Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below.: **None**

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation

Move person to fresh air. If breathing is laboured, administer oxygen. If symptoms persist, obtain medical attention.

Skin Contact

Wash affected skin with soap and water. If symptoms develop, obtain medical attention.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

If symptoms develop, obtain medical attention. Treat symptomatically.

Most important symptoms and effects, both acute and delayed

None

Indication of any immediate medical attention and special treatment needed

None



SLIDE MOLD & METAL POLISH

Issue Date: 6-May-2015

Revision Date: 6-May-2015

Version 1

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media As appropriate for surrounding fire. Product is not classified as flammable, but will burn on contact with flame or exposure to high temperature.

-Unsuitable Extinguishing Media None known.

Special hazards arising from the substance or mixture None known.

Advice for fire-fighters A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Not normally required. Wear protective gloves/eye protection.

Environmental precautions Not normally required. Contain effluent and prevent effluent from entering sewers and waterways.

Methods and material for containment and cleaning up Transfer to a container for disposal or recovery.

Reference to other sections None

Additional Information None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling Avoid contact with skin and eyes. Wear protective gloves/eye protection. Avoid breathing vapours. Wash hands and exposed skin after use.

Conditions for safe storage, including any incompatibilities

-Storage temperature Store at room temperature. Do not allow material to freeze.

-Incompatible materials None known

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

| SUBSTANCE. | CAS No. | (8hr TWA) | | STEL | | Note: |
|------------------|---------|------------|-------------|------------|-------------|-------|
| | | PEL (OSHA) | TLV (ACGIH) | PEL (OSHA) | TLV (ACGIH) | |
| Alkanes (C9-C15) | ----- | ----- | 1200 mg/m3 | ----- | ----- | ----- |

Recommended monitoring method NIOSH 1550 (Naphthas)

Appropriate engineering controls No special measures are required.

Personal protection equipment

SLIDE MOLD & METAL POLISH

Issue Date: 6-May-2015

Revision Date: 6-May-2015

Version 1

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber or Butyl rubber). Check with protective equipment manufacturer's data.

Respiratory protection



Normally no personal respiratory protection is necessary.

Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

Environmental Exposure Controls

Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | |
|--|-------------------|
| Appearance | Paste |
| Color. | Pinkish |
| Odor | Slight Ammonia |
| Odor Threshold (ppm) | Not available |
| pH (Value) | 7 |
| Melting Point (°C) / Freezing Point (°C) | Not available |
| Boiling point/boiling range (°C): | 70 (158 °F) |
| Flash Point (°C) | > 93.3 (> 200 °F) |
| Evaporation Rate | Not available |
| Flammability (solid, gas) | Not available |
| Explosive Limit Ranges | Not available |
| Vapour pressure (Pascal) | Not available |
| Vapour Density (Air=1) | Not available |
| Density (g/ml) | 1.09 |
| Solubility (Water) | Insoluble |
| Solubility (Other) | Not available |
| Partition Coefficient (n-Octanol/water) | Not available |
| Auto Ignition Point (°C) | Not available |
| Decomposition Temperature (°C) | Not available |
| Kinematic Viscosity (cSt) | > 20.5 @ 40 °C |
| Explosive properties | Not explosive. |
| Oxidizing properties | Not oxidizing. |

Other information

VOC Content: 2.569 lb/gal

SECTION 10: STABILITY AND REACTIVITY

| | |
|---|---------------------------------|
| Reactivity | Stable under normal conditions. |
| Chemical stability | Stable. |
| Possibility of hazardous reactions | None anticipated. |
| Conditions to avoid | None known |
| Incompatible materials | None known |
| Hazardous decomposition product(s) | None known |



SLIDE MOLD & METAL POLISH

Issue Date: 6-May-2015

Revision Date: 6-May-2015

Version 1

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Skin Contact, Eye Contact

Information on toxicological effects

Petroleum Distillate (CAS No. 64742-48-9 & 64742-88-7) - By analogy with similar materials:

Acute toxicity Oral: LD50 >5000 mg/kg-bw
 Dermal: LD50 >2000 mg/kg-bw
 Inhalation: LC0 > 5.6 mg/l (Vapor), 4-hr. rat - May cause drowsiness or dizziness.

Irritation/Corrosivity Causes skin irritation.

Sensitization It is not a skin sensitizer.

Repeated dose toxicity Oral: LOAEL 500 mg/kg
 Dermal: NOEAL > 2000 ml/kg bw
 Inhalation: NOAEL ≥1000 mg/m3

Carcinogenicity It is unlikely to present a carcinogenic hazard to man.

| NTP | IARC | ACGIH | OSHA | NIOSH |
|-----|------|-------|------|-------|
| No. | No. | No. | No. | No. |

Mutagenicity Not to be expected
Reproductive toxicity Not to be expected

SECTION 12: ECOLOGICAL INFORMATION

Substances in preparations / mixtures:

Petroleum Distillate (CAS No. 64742-48-9 & 64742-88-7) - By analogy with similar materials:

Acute toxicity LL50 (96 hour) = 8.2 mg/l (*Pimephales promelas*)
 EL50 (48 hour) = 4.5 mg/l (*Daphnia magna*)

Long Term Toxicity NOELR (21 days) = 2.6 mg/l (*Daphnia magna*)
 NOELR (72 hour) = 0.5 mg/L (*Pseudokirchnerella subcapitata*)

Persistence and degradability According to OECD criteria the substance is not readily biodegradable but inherently biodegradable.

Bioaccumulative potential The substance has no potential for bioaccumulation.

Mobility in soil No data.

Results of PBT and vPvB assessment Not classified as PBT or vPvB.

Other adverse effects None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

SECTION 14: TRANSPORT INFORMATION

| | Land transport (U.S. DOT) | Sea transport (IMDG) | Air transport (ICAO/IATA) |
|----------------------|--|-------------------------|------------------------------|
| UN number | | | |
| Proper Shipping Name | Not classified as dangerous for transport. | | |



SLIDE MOLD & METAL POLISH

Issue Date: 6-May-2015

Revision Date: 6-May-2015

Version 1

Transport hazard class(es)
Packing group
Environmental hazards
Special precautions for user

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

| Chemical Name | CAS No. | Typical %wt. | RQ (Pounds) |
|---------------|---------|--------------|-------------|
| None | ---- | ---- | ---- |

SARA 311/312 - Hazard Categories:

Fire Sudden Release Reactivity Immediate (acute) Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

| Chemical Name | CAS No. | Typical %wt. |
|---------------|---------|--------------|
| None | ---- | ---- |

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

| Chemical Name | CAS No. | Typical %wt. | TPQ (pounds) |
|---------------|---------|--------------|--------------|
| None | ---- | ---- | ---- |

California Proposition 65 List:

| Chemical Name | CAS No. | Type of Toxicity |
|---------------|---------|------------------|
| None | ---- | ---- |

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: April 30, 2015

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.